

**XMM Flight Operation Procedures
(Version 2 and following updates)**

**Change and comments for the EPIC MOS 1&2 instruments
(EPIC-EST-TN-010)**

Nicola La Palombara

This document summarises all the changes to be implemented in the currently existing XMM Flight Operation Procedures relevant to the EPIC MOS instruments (Issue 2 and following updates up to Delta 2.6).

Only the latest Issue of each Procedure or Sequence has been considered. Therefore, in order to avoid repetitions, the changes are sorted in reverse order: from Delta 2.6 back to Delta 2.2 and, eventually, FOP v2.

For each procedure or sequence, it is reported the step where at least one parameter has to be modified: the new parameter value(s) are shown in ***bold slanted*** characters.

Delta 2.6

FCP_EM1_0110 (1,1) - FF FIXED OTS

ES4100 – SET FP TEMP (Step 1)

E0129 "VACUUMSENSORSTAT" = ***OFF***

ES2100 – SET_CCD_VOLTS (Step 2)

Confirm they are the last updated values

ES2600 - SET HBR DEFAULTS (Step 3)

E0079 "FASTPATTERNTHRES" = ***3***

ES2610 - SET_HBR_BPTS (Step 4)

Now these data have been updated

ES2150 - ZERO AND START SEQ PCS (Step 9.6)

E0133 "EMAECOMMANDADDR." = 33 (Sequencer/Port Control for AnChains 1&2)

E0160 "EMAECOMMANDDATUM" = ***129***

ES1400 - CONFIG GENERAL (Step 11)

E0176 "ANCH1/2 INTSIMUL" = 1 (as before, but which means *AnChain1-Normal-Node0*)

FCP_EM1_7901 (1,1) - LW SUPER ED

ES2150 - ZERO AND START SEQ PCS (Step 6)

E0133 "EMAECOMMANDADDR." = 33 (Sequencer/Port Control for AnChains 1&2)

E0160 "EMAECOMMANDDATUM" = ***129***

ES1400 - CONFIG GENERAL (Step 6.1)

E0176 "ANCH1/2 INTSIMUL" = 1 (as before, but which means *AnChain1-Normal-Node0*)

FCP_EM1_7902 (1,1) - SW SUPER ED

ES2150 - ZERO AND START SEQ PCS (Step 6)

E0133 "EMAECOMMANDADDR." = 33 (Sequencer/Port Control for AnChains 1&2)

E0160 "EMAECOMMANDDATUM" = ***129***

ES1400 - CONFIG GENERAL (Step 6.1)

E0176 "ANCH1/2 INTSIMUL" = 1 (as before, but which means *AnChain1-Normal-Node0*)

FCP_EM1_7911 (1,0) - FF SUPER ED FIXED OTS

ES1400 - CONFIG GENERAL (Step 6.1)

E0176 "ANCH1/2 INTSIMUL" = 1 (as before, but which means *AnChain1-Normal-Node0*)

FCP_EM1_7990 (1,0) - IM SWITCH TO LOW GAIN**ES2801 - SET GAIN LO (Step 3.1)**E0176 "ANCH1/2 INTSIMUL" = 1 (as before, but which means *AnChain1-Normal-Node0*)**FCP_EM1_7991 (1,0) - TI SWITCH TO LOW GAIN****ES2801 - SET GAIN LO (Step 3.1)**E0176 "ANCH1/2 INTSIMUL" = 1 (as before, but which means *AnChain1-Normal-Node0*)**SEQ_EM1_2444 (1,0) - SET EDU WINS FF/TI (Step 2)**

E0104 "EDU IDENTIFIER" = 0

E0139 "WINDOW X0" = 255

E0140 "WINDOW Y0" = 0

E0141 "WINDOW X SIZE" = 100

E0142 "WINDOW Y SIZE" = 602 (right only for Diagnostic, *1* for O&V, *0* for Observation)**SEQ_EM1_5500 (1,0) - SW INSTANCES**

The maximum memory length for the EMDH memory dump is 7FFF=32767 and not FFFF=65535, therefore the 3 dumps must be performed as follows:

First dump = 0x1A000 to 0x3FFFF

E0051 - DUMP EMDH MEMORYE0300 "START ADDRESS" = **106496**E0301 "LENGTH" = **32767****E0051 - DUMP EMDH MEMORY**E0300 "START ADDRESS" = **139263**E0301 "LENGTH" = **32767****E0051 - DUMP EMDH MEMORY**E0300 "START ADDRESS" = **172030**E0301 "LENGTH" = **32767****E0051 - DUMP EMDH MEMORY**E0300 "START ADDRESS" = **204797**E0301 "LENGTH" = **32767****E0051 - DUMP EMDH MEMORY**E0300 "START ADDRESS" = **237564**E0301 "LENGTH" = **24580**

Second dump = 0x9E000 to 0xC8A3B

E0051 - DUMP EMDH MEMORYE0300 "START ADDRESS" = **647168**E0301 "LENGTH" = **32767****E0051 - DUMP EMDH MEMORY**E0300 "START ADDRESS" = **679935**E0301 "LENGTH" = **32767****E0051 - DUMP EMDH MEMORY**E0300 "START ADDRESS" = **712702**E0301 "LENGTH" = **32767****E0051 - DUMP EMDH MEMORY**E0300 "START ADDRESS" = **745469**E0301 "LENGTH" = **32767****E0051 - DUMP EMDH MEMORY**E0300 "START ADDRESS" = **778236**E0301 "LENGTH" = **32767****E0051 - DUMP EMDH MEMORY**E0300 "START ADDRESS" = **811003**E0301 "LENGTH" = **10817**

Last dump = 0xC8A41 to 0xCB538

E0051 - DUMP EMDH MEMORY
 E0300 "START ADDRESS" = **821825**
 E0301 "LENGTH" = **11000**

SEQ_EM1_7036 (1,0) - LW DIAG EXP

The number of expected pixels for the LW diagnostic is 310x300=93000 and not 610x602=367220 as in FF mode. Therefore the sequence has to be changed as follows:

E0006 - ENTER CCDD MODE (Step 3)
 E0001 "REJECTED FRAMES" = 5
 E0002 "EXP. FRAME PIXEL" = **93000**

SEQ_EM1_7056 (1,0) - TI DIAGNOSTIC

Since a "frame" in Timing mode is just a binned row, the number of rejected frames has to be changed as follows:

E0006 - ENTER CCDD MODE (Step 3)
 E0001 "REJECTED FRAMES" = **3010**
 E0002 "EXP. FRAME PIXEL" = 60200

EVD_EM1_7000 (1,1) - FF SUPER ED

ES2150 - ZERO AND START SEQ PCS (Step 6)
 E0133 "EMAECOMMANDADDR." = 33 (Sequencer/Port Control for AnChains 1&2)
 E0160 "EMAECOMMANDDATUM" = **129**
ES1400 - CONFIG GENERAL (Step 6.1)
 E0176 "ANCH1/2 INTSIMUL" = 1 (as before, but which means *AnChain1-Normal-Node0*)
ES1500 - FF INT TIME (Step 6.4)
 E0148 "EMCRGROUP1INTTIM" = **2.6** sec
 E0149 "EMCRGROUP2INTTIM" = **2.6** sec
 E0150 "EMCRGROUP3INTTIM" = **2.6** sec
 E0151 "EMCRGROUP4INTTIM" = **2.6** sec

Delta 2.5

FCP_EM1_1109 (1,3) - OFFSET VARIANCE

ES2150 - ZERO AND START SEQ PCS (Step 2.6)
 E0133 "EMAECOMMANDADDR." = 33 (Sequencer/Port Control for AnChains 1&2)
 E0160 "EMAECOMMANDDATUM" = **129**
ES1400 - CONFIG GENERAL (Step 2.8)
 E0176 "ANCH1/2 INTSIMUL" = 1 (as before, but which means *AnChain1-Normal-Node0*)
ES2150 - ZERO AND START SEQ PCS (Step 11)
 E0133 "EMAECOMMANDADDR." = 33 (Sequencer/Port Control for AnChains 1&2)
 E0160 "EMAECOMMANDDATUM" = **129**

FCP_EM1_1114 (1,3) - THRESHOLD

ES1400 - CONFIG GENERAL (Step 2.7)
 E0176 "ANCH1/2 INTSIMUL" = 1 (as before, but which means *AnChain1-Normal-Node0*)

At Step 2.8 "Set integration time", sequence **EE1500 - FF INT TIME** must be replaced with **EE1504 - RFS INT TIME**, since the Refreshed Frame Store EMAE sequences were uploaded.

FCP_EM1_1124 (1,0) - THRESHOLD LO GAIN

In order to readout data in Low Gain mode from Node 0 of all CCDs, the following changes must be implemented:

EE1401 - CONFIG CCD1 (Step 2.6)
 E0133 "EMAECOMMANDADDR." = 33 (Sequencer/Port Control for AnChains 1&2)

E0160 "EMAECOMMANDDATUM" = **130**
 E0133 "EMAECOMMANDADDR." = 97 (Sequencer/Port Control for AnChains 3&4)
 E0160 "EMAECOMMANDDATUM" = **130**
 E0133 "EMAECOMMANDADDR." = 161 (Sequencer/Port Control for AnChains 5&6)
 E0160 "EMAECOMMANDDATUM" = **130**
 E0133 "EMAECOMMANDADDR." = 225 (Sequencer/Port Control for AnChains 7&8)
 E0160 "EMAECOMMANDDATUM" = **130**

ES1400 - CONFIG GENERAL (Step 2.7)

E0215 ' ' ANCHAIN2PWON/OFF' ~~ON~~
 E0214 ' ' ANCHAIN1PWON/OFF' ~~OFF~~
 E0176 "ANCH1/2 INTSIMUL" = **2** (Analogue Chain2_/10 - Node 0)
 E0183 "ANCH3/4 INTSIMUL" = **2** (Analogue Chain_/10 - Node 0)
 E0190 "ANCH5/6 INTSIMUL" = **2** (Analogue Chain_/10 - Node 0)
 E0197 "ANCH7/8 INTSIMUL" = **2** (Analogue Chain_/10 - Node 0)

EE2411 - SET_EDU_THRESHOLDS-ZERO (Step 2.9)

E0112 ' ' EDU 0 OPER. MODE' **STOP**
 E0113 ' ' EDU 1 OPER. MODE' **RUN**

EE2430 - ZERO_NORM_OFFSET_TABLES (Step 2.11)

E0104 ' ' EDU IDENTIFIER' ' = 1
 E0108 ' ' OST IDENTIFIER' ' = 0
 E0105 ' ' EDU ZONE' **NORMAL AREA**

EE7115 - FF OFFSET CCD1 (Step 3.1)

E0039 "HBR 1 PROCESSING" = **DISABLED**
 E0040 "HBR 2 PROCESSING" = **TRANSPARENT**
 E0104 ' ' EDU IDENTIFIER' **1** =
 E0108 ' ' OST IDENTIFIER' ' = 7
 E0105 ' ' EDU ZONE' ' = NORMAL AREA

EE2415 - SET EDU THRESHOLDS – TH (Step 10)

E0112 ' ' EDU 0 OPER. MODE' **STOP**
 E0120 ' ' EDU 0 SCIEN.MODE' **TRANSPARENT**
 E0113 "EDU 1 OPER. MODE" = **RUN**
 E0121 "EDU 1 SCIEN.MODE" = **THRESHOLD**

EE7123 - TH START EXP (Step 11.1)

E0039 ' ' HBR 1 PROCESSING' **DISABLED**
 E0040 ' ' HBR 2 PROCESSING' **EDU THRESH.**

At Step 2.8 “Set integration time”, sequence **EE1500** - FF INT TIME must be replaced with **EE1504** - RFS INT TIME, since the Refreshed Frame Store EMAE sequences were uploaded.

FCP_EM1_1201 (1,0) - SLEW START

ES1400 - CONFIG GENERAL (Step 1.4)

E0176 "ANCH1/2 INTSIMUL" = 1 (as before, but which means *AnChain1-Normal-Node0*)

FCP_EM1_7900 (1,0) - FF SUPER ED

ES1400 - CONFIG GENERAL (Step 6.1)

E0176 "ANCH1/2 INTSIMUL" = 1 (as before, but which means *AnChain1-Normal-Node0*)

ES1500 - FF INT TIME (Step 6.4)

E0148 "EMCRGROUP1INTTIM" = **2.6** sec
 E0149 "EMCRGROUP2INTTIM" = **2.6** sec
 E0150 "EMCRGROUP3INTTIM" = **2.6** sec
 E0151 "EMCRGROUP4INTTIM" = **2.6** sec

Delta 2.2**FCP_EM1_1102 (1,3) - LARGE WINDOW****ES1400 - CONFIG GENERAL** (Step 2.4)E0176 "ANCH1/2 INTSIMUL" = 1 (as before, but which means *AnChain1-Normal-Node0*)**FCP_EM1_1103 (1,3) - SMALL WINDOW****ES1400 - CONFIG GENERAL** (Step 2.4)E0176 "ANCH1/2 INTSIMUL" = 1 (as before, but which means *AnChain1-Normal-Node0*)**FCP_EM1_1104 (1,3) - TIMING****ES1400 - CONFIG GENERAL** (Step 2.4)E0176 "ANCH1/2 INTSIMUL" = 1 (as before, but which means *AnChain1-Normal-Node0*)**EE1520 - TI INT TIME** (Step 2.5)

E0148 "EMCRGROUP1INTTIM" = 102.4 sec

E0149 "EMCRGROUP2INTTIM" = **2.6** secE0150 "EMCRGROUP3INTTIM" = **2.6** secE0151 "EMCRGROUP4INTTIM" = **2.6** sec**EE7415 - TI OFFSET CCD1** (Step 3.1)E0139 ' ' WINDOW XO' **255**E0246 ' ' INITIAL MEDIAN' **100**E0247 ' ' INITIAL SIGMA' **20****EE1441 - TI CONFIG CCD1** (Step 10.3)E0142 ' ' WINDOW Y SIZE' **0** (to be considered as 1024)**FCP_EM1_1106 (1,4) - LARGE WINDOW FREE RUNNING****ES1400 - CONFIG GENERAL** (Step 2.4)E0176 "ANCH1/2 INTSIMUL" = 1 (as before, but which means *AnChain1-Normal-Node0*)**EE1520 - TI INT TIME** (Step 2.5)

E0148 "EMCRGROUP1INTTIM" = 102.4 sec

E0149 "EMCRGROUP2INTTIM" = **2.6** secE0150 "EMCRGROUP3INTTIM" = **2.6** secE0151 "EMCRGROUP4INTTIM" = **2.6** sec**FCP_EM1_1107 (1,3) - SMALL WINDOW FREE RUNNING****ES1400 - CONFIG GENERAL** (Step 2.4)E0176 "ANCH1/2 INTSIMUL" = 1 (as before, but which means *AnChain1-Normal-Node0*)**EE1520 - TI INT TIME** (Step 2.5)

E0148 "EMCRGROUP1INTTIM" = 102.4 sec

E0149 "EMCRGROUP2INTTIM" = **2.6** secE0150 "EMCRGROUP3INTTIM" = **2.6** secE0151 "EMCRGROUP4INTTIM" = **2.6** sec**FCP_EM1_1108 (1,3) - TIMING COMPRESSED****ES1400 - CONFIG GENERAL** (Step 2.4)E0176 "ANCH1/2 INTSIMUL" = 1 (as before, but which means *AnChain1-Normal-Node0*)**EE1520 - TI INT TIME** (Step 2.5)

E0148 "EMCRGROUP1INTTIM" = 102.4 sec

E0149 "EMCRGROUP2INTTIM" = **2.6** secE0150 "EMCRGROUP3INTTIM" = **2.6** secE0151 "EMCRGROUP4INTTIM" = **2.6** sec**EE7415 - TI OFFSET CCD1** (Step 3.1)

E0139 ' ' WINDOW XO' **255**
 E0246 ' ' INITIAL MEDIAN' **100**
 E0247 ' ' INITIAL SIGMA' **20-**

EE1441 - TI CONFIG CCD1 (Step 10.3)

E0142 ' ' WINDOW Y SIZE' **0** (to be considered as 1024)

FCP_EM1_1111 (1,3) - DOUBLE NODE

ES1410 - CONFIG GENERAL - D.N. (Step 2.4)

E0176 "ANCH1/2 INTSIMUL" = 1 (as before, but which means *AnChain1-Normal-Node0*)

EE7515 - DN OFFSET CCD1 (Step 3)

E0141 ' ' WINDOW X SIZE' **310**
 E0243 ' ' CCD MODE' **IMAGINGWINDOW**
 E0250 ' ' FIELD OF VIEW P1' **0** =
 E0251 ' ' FIELD OF VIEW P2' **0** =
 E0252 ' ' FIELD OF VIEW P3' **0** =
 E0253 ' ' FIELD OF VIEW P4' **0** =
 E0254 ' ' FIELD OF VIEW P5' **0** =
 E0255 ' ' FIELD OF VIEW P6' **0** =
 E0256 ' ' FIELD OF VIEW P7' **0** =
 E0257 ' ' FIELD OF VIEW P8' **0** =
 E0300 ' ' START ADDRESS' **80432**
 E0300 ' ' START ADDRESS' **80738**

EE7525 - DN OFFSET CCD1 ALTERNATE (Step 4)

E0141 ' ' WINDOW X SIZE' **310**
 E0242 ' ' READOUT NODE' **1** =
 E0243 ' ' CCD MODE' **IMAGINGWINDOW**
 E0250 ' ' FIELD OF VIEW P1' **0** =
 E0251 ' ' FIELD OF VIEW P2' **0** =
 E0252 ' ' FIELD OF VIEW P3' **0** =
 E0253 ' ' FIELD OF VIEW P4' **0** =
 E0254 ' ' FIELD OF VIEW P5' **0** =
 E0255 ' ' FIELD OF VIEW P6' **0** =
 E0256 ' ' FIELD OF VIEW P7' **0** =
 E0257 ' ' FIELD OF VIEW P8' **0** =
 E0300 ' ' START ADDRESS' **80432**
 E0300 ' ' START ADDRESS' **80738**

FCP_EM1_1120 (1,1) - DIAGNOSTIC RPP

ES1400 - CONFIG GENERAL (Step 2.6)

E0176 "ANCH1/2 INTSIMUL" = 1 (as before, but which means *AnChain1-Normal-Node0*)

SEQ_EM1_1503 (1,0) - DN INT TIME

E0152 ' ' EMCR2FIRSTCYCDEL' **0** sec

SEQ_EM1_2422 (2,1) - SW PATCH OT

EU055 - LOAD TABLES TC3 (Step 3.1)

E0300 "START ADDRESS" = **80788**

SEQ_EM1_2423 (2,1) - LW PATCH OT

EU055 - LOAD TABLES TC3 (Step 3.1)

E0300 "START ADDRESS" = **80888**

SEQ_EM1_2424 (2,1) - DN PATCH OT

EU055 - LOAD TABLES TC3 (Step 2.1)

E0300 "START ADDRESS" = **80432**

EU055 - LOAD TABLES TC3 (Step 3.1)

E0300 "START ADDRESS" = **80738**

SEQ_EM1_7215 (2,0) - FF OFFSET CCD1N2

E0005 - ENTER O MODE (Step 5)

E0242 ' ' READOUT NODE' **1** =

SEQ_EM1_7245 (2,0) - TI OFFSET CCD1

E0005 - ENTER O MODE (Step 5)

E0139 ' ' WINDOW XO' **255**

E0246 ' ' INITIAL MEDIAN' **100**

E0247 ' ' INITIAL SIGMA' **20**=

FOP v2

FCP_EM1_0010 (1,2) - BASIC CONFIG.

ES4100 - SET FP TEMP (Step 1)

E0129 "VACUUMSENSORSTAT" = **OFF**

FCP_EM1_0100 (1,2) - REF. CONFIG.

ES2150 - ZERO AND START SEQ PCS (Step 4.6)

E0133 "EMAECOMMANDADDR." = 33 (Sequencer/Port Control for AnChains 1&2)

E0160 "EMAECOMMANDDATUM" = **129**

FCP_EM1_1101 (1,2) - PRIME FULL WINDOW

EE1400 - CONFIG GENERAL (Step 2.4)

E0176 "ANCH1/2 INTSIMUL" = 1 (as before, but which means *AnChain1-Normal-Node0*)

EE1500 - FF INT TIME (Step 2.5)

E0148 "EMCRGROUP1INTTIM" = **2.6** sec

E0149 "EMCRGROUP2INTTIM" = **2.6** sec

E0150 "EMCRGROUP3INTTIM" = **2.6** sec

E0151 "EMCRGROUP4INTTIM" = **2.6** sec

FCP_EM1_1110 (1,2) - DIAGNOSTIC

EE1400 - CONFIG GENERAL (Step 2.4)

E0176 "ANCH1/2 INTSIMUL" = 1 (as before, but which means *AnChain1-Normal-Node0*)

EE1500 - FF INT TIME (Step 2.5)

E0148 "EMCRGROUP1INTTIM" = **2.6** sec

E0149 "EMCRGROUP2INTTIM" = **2.6** sec

E0150 "EMCRGROUP3INTTIM" = **2.6** sec

E0151 "EMCRGROUP4INTTIM" = **2.6** sec